

DATAMASTER[®]

INSTRUMENTATION CABLE

Our instrumentation cables are suitable for a wide range of applications across industries where manufacturing and processing operations are controlled and measured by electronic means. Predominantly used as access control cable in commercial air conditioning installation.

DATAMASTER Y4806100/Y4806200 (2PR 1.5mm²)

- Max.Conductor(A) DC Resistance at 20-c (n/100M) < 1.40
- Min.Insulation DC Resistance at 20-c < Mn*M I >200
- Operating temperature(°C) -20°C - +50°C
- Rated Voltage (V) 300V
- Al-Foil and Mylar Shields
- Inner Conductor 4/BC0.50(+/-0.010)mmx7 - Stranded Bare Copper
- 4/2.25(+/-0.13)mm Insulation - FR-PVC Insulation (2*black, 2*white)
- TC0.25(+/-0.008)mmx7 Drain - Stranded Tinned Copper



DATAMASTER Y4805100/Y4805200 (1PR 1.5mm²)

- Max.Conductor(A) DC Resistance at 20-c (n/100M) < 1.40
- Min.Insulation DC Resistance at 20-c < Mn*M I >200
- Operating temperature(°C) -20°C - +80°C
- Rated Voltage (V) 300V
- Al-Foil and Mylar Shields
- Inner Conductor 2/BC0.50(+/-0.010)mmx7 - Stranded Bare Copper
- 2/2.25(+/-0.13)mm Insulation - FR-PVC Insulation (black, white)
- TC0.25(+/-0.008)mmx7 Drain - Stranded Tinned Copper
- 6.30 (+/-0.25)mm - BLACK FR-PVC Sheath



For the full range of DATAMASTER cables, cabinets and related products, contact your local sales representative or visit our website below.

WWW.ACCESSCOMMS.COM.AU



Sydney (Head Office)
33-35 Alleyne Street,
Chatswood NSW 2067
Phone: (02) 9414 8888
Fax: (02) 9414 8800

Melbourne
24 Mareno Road,
Tullamarine VIC 3043
Phone: (03) 9330 8333
Fax: (03) 9330 8330

Brisbane
Unit 4, 7 Luke Street,
Lytton QLD 4178
Phone: (07) 3308 5555
Fax: (07) 3308 5500

Adelaide
427 Portrush Road,
Toorak Gardens SA 5065
Phone: 0438 245 116