

## Horn Speaker 15 Watt 8 Ohm

K3505



### FEATURES

- 15-Watt horn speaker suitable for connection to the K3507 Tone Ringer and K3509 Universal Loud Sounding Alarm.
- Features a 350mm figure-8 cable with tinned ends for easy connection. Rated IP54 for splash-proof protection.
- Colour: White

### SPECIFICATIONS

ITEM	DESCRIPTION	SPECIFICATION	TEST CONDITION
1	Voice Coil Impedance	8 Ohm $\pm$ 15 %	AT 1K Hz
2	Voice Coil Size	(Dia.) 25.4mm	
3	Magnet Size	70mm x 32mm x 10mm	Weight 5.4 Oz
4	Operation	MUST BE NORMAL	Program Source V
5	Buzzes & Rattles	MUST BE NORMAL	Sin Wave V
6	Resonant Frequency	500 Hz $\pm$ 20 % Hz	Without Baffle
7	Frequency Response	fo ~ 10K Hz	
8	Rated Frequency Response	450 ~ 10K Hz	
9	Rated Power Input	25 Watts	
10	R.M.S. Power Input	15 Watts	
11	Load Test	AFTER TESTED 4 & 5	White Noise 15 Watts 1 Hours
12	Net Weight	770 Grams $\pm$ 10 Grams	
13	Output S.P.L.	Mean value at 102 $\pm$ 3 dB	AT 1 M 1 Watt Axis CAL.
14	IP Rating	IP54 splash-proof protection	

To view Access' extensive ranges go to: [www.accesscomms.com.au](http://www.accesscomms.com.au)

**Sydney (Head Office)**  
**Brisbane Sales**  
**Melbourne Office**  
**Adelaide Office**

Unit 1, 29 Prince William Drive, Seven Hills NSW 2147  
28 The Gateway, Broadmeadows VIC 3047  
71 Anzac Highway, Ashford SA 5035

Phone: (02) 9414 8888  
Phone: (07) 3308 5555  
Phone: (03) 9330 8333  
Phone: (08) 8338 5540

[sales@accesscomms.com.au](mailto:sales@accesscomms.com.au)  
[brisbane@accesscomms.com.au](mailto:brisbane@accesscomms.com.au)  
[melbourne@accesscomms.com.au](mailto:melbourne@accesscomms.com.au)  
[adelaide@accesscomms.com.au](mailto:adelaide@accesscomms.com.au)