

FEATURES

The Datamaster 2-port HDMITM 4K switch lets you share a display or projector with two HDMITM-enabled video sources. The switch features two independent inputs that each support 4K resolution and 7.1 surround sound audio. You'll be amazed at how this video switch maintains Ultra HD picture quality. 4K is supported by the latest A/V devices and delivers four times the resolution of 1080p. Plus, because the switch is backward compatible with high-definition 1080p, you can rest assured any video source will look great in your digital signage application.

Enjoy hassle-free operation with three different switching modes:

- Supports manual switching.
- Remote control switching and automatic switching.
- Supports HDCP 2.2.
- Supports high Definition resolution 4K@60Hz and Full 3D
- Supports 600MHz/6.0Gbps per channel bandwidth (18Gbps all channels)
- Supports Consumer Electronics Control
- Supports 12bit per channel (36bit all channels) deep color
- Supports uncompressed audio such as LPCM
- Supports compressed audio such as DTS, Dolby Digital[™] including DTS-HD Master AudioTM and Dolby TrueHD[™] Note: Dolby is a trademark of Dolby Laboratories.

To view Access' extensive ranges go to: www.accesscomms.com.au

Sydney (Head Office) Brisbane Sales Melbourne Office Adelaide Office Unit 1, 29 Prince William Drive, Seven Hills NSW 2147

28 The Gateway, Broadmeadows VIC 3 71 Anzac Highway, Ashford SA 5035 Phone: (02) 9414 8888 Phone: (07) 3308 5555 Phone: (03) 9330 8333 Phone: (08) 8338 5540 sales@accesscomms.com.au brisbane@accesscomms.com.au melbourne@accesscomms.com.au adelaide@accesscomms.com.au

DATAMASTER HDMI 4K2K Switch 2 in 1 Out P07712



TECHNICAL CHARACTERISTICS

Video Input	2 x HDMI 2.0
Video Output	1 x HDMI 2.0
Frequency Range	50 / 60 Hz
Video Amplifier Bandwidth	6.0 Gbps / 600MHz per channel
Interlaced (50/60 Hz)	480i, 576i, 1080i
Progressive(50/60Hz)	480P, 576P, 720P, 1080P, 4K2K
Limited Warranty	1 Year
Operating Temperature	0°C to + 70°C
Operating Humidity	10% to 85% RH (No condensation)
Storage Temperature	-10°C to +80°C
Storage Humidity	5% to 90% RH (No condensation)
External Power Supply	5V DC 1A
Power Consumption (Max)	2W

To view Access' extensive ranges go to: www.accesscomms.com.au

Sydney (Head Office) Brisbane Sales Melbourne Office Adelaide Office Unit 1, 29 Prince William Drive, Seven Hills NSW 2147

28 The Gateway, Broadmeadows VIC 3047 71 Anzac Highway, Ashford SA 5035 Phone: (02) 9414 8888 Phone: (07) 3308 5555 Phone: (03) 9330 8333 Phone: (08) 8338 5540 sales@accesscomms.com.au brisbane@accesscomms.com.au melbourne@accesscomms.com.au adelaide@accesscomms.com.au