



## Cat6A Shielded 8 Position Modular Plug

P2178UJ

### ELECTRICAL SPECIFICATIONS

|                                 |                                       |
|---------------------------------|---------------------------------------|
| UL Applications                 | 250 Volts AC Max at 2 AMPS            |
| Dielectric Withstanding Voltage | 500V AC                               |
| Insulation Resistance           | 100 MΩ                                |
| Termination                     | 20 MΩ Max after environmental testing |

### MATERIAL SPECIFICATIONS

|               |                               |
|---------------|-------------------------------|
| Housing       | Polycarbonate UL4V-2          |
| Colour        | Transparent                   |
| Contact Blade | 50μ" Gold Plated Copper Alloy |

### MECHANICAL SPECIFICATIONS

|                                |                   |
|--------------------------------|-------------------|
| Cable to plug tensile strength | 200 Pound Min     |
| Durability                     | 200 Mating Cycles |

### SUITS

Suits stranded and solid conductors 22 - 23 AWG



To view Access' extensive ranges go to: [www.accesscomms.com.au](http://www.accesscomms.com.au)

**Sydney (Head Office)**  
**Brisbane Sales**  
**Melbourne Office**  
**Adelaide Office**

Unit 1, 29 Prince William Drive, Seven Hills NSW 2147  
28 The Gateway, Broadmeadows VIC 3047  
71 Anzac Highway, Ashford SA 5035

Phone: (02) 9414 8888  
Phone: (07) 3308 5555  
Phone: (03) 9330 8333  
Phone: (08) 8338 5540

[sales@accesscomms.com.au](mailto:sales@accesscomms.com.au)  
[brisbane@accesscomms.com.au](mailto:brisbane@accesscomms.com.au)  
[melbourne@accesscomms.com.au](mailto:melbourne@accesscomms.com.au)  
[adelaide@accesscomms.com.au](mailto:adelaide@accesscomms.com.au)