DATAMASTER




4 Conductor Double Insulated Speaker Cable Y3460 Series



FEATURES

- Quality high grade, double insulated 2-conductor speaker cable with Yellow PVC jacket.
- Applications include surround sound speaker cabling and PA.
- Available on 100 metre, wooden reels or 200 metre pull-boxes.
- Count-down metre-marking.
- Other jacket colours can be custom made upon request.

DESIGN & CONSTRUCTION



	DESCRIPTION	COLOUR	SPECIFICATION	MATERIALS
Α	Conductor		4 x 65 / 0.16 (± 0.008)mm (16AWG)	Stranded Bare Copper
В	Conductor Insulation	Green / Red / White / Black	4 x 2.30 (± 0.15) mm	FR-PVC
С	Rip Cord			Nylon
D	Sheath	Yellow	6.40 (± 0.25)mm	FR-PVC

DATAMASTER



4 Conductor Double Insulated Speaker Cable Y3460 Series

ELECTRICAL CHARACTERISTICS				
Minumum conductor DC resistance	< 1.58 Ω / 1000 metres @20°C			
Minimum insulation DC resistance	> 200M Ω / Metres @ 20°C			
Rated temperature	80°C			
Rated Voltage	300V			

PHYSICAL CHARACTERISTICS				
Minimum Bending Radius	15 x Dmm			
Conductor Elongation	> 15% (at breaking point)			
Sheath Tensile Strength	10.00N/mm ²			
Sheath Elongation at break	125.0% (at breaking point)			

PACKING	PACKING		
Y3461YEL	100 metre reel		
Y3462YEL	200 metre reel		