



Security Cable Pull Box White & Grey

Y4141GRY, Y4143GRY, Y4141WHI, Y4143WHI
Y4144WHI, Y4241GRY, Y4243GRY, Y4244GRY
Y4241WHI, Y4243WHI, Y4244WHI, Y4244BRN,
Y4244BLK



FEATURES

High-performance LAN Cable is suitable for perfect audio data video or transfer for outdoor burial horizontal network. Suitable below ground installation. Multicore 4 conductor cable for security applications with either 7/0.20mm² or 14/0.20mm² stranding. Supplied on 100 and 305 metre strong polypropylene reels or 305 metre pull-boxes, all with count-down metre-marking. Other reel sizes or jacket colours can be custom made.



DESIGN & CONSTRUCTION

ITEM	Number / Millimetre	AQL	DESCRIPTION
Conductor	4 x 14 / 0.20 OR 4 x 7 / 0.20	0.20 (± 0.008)	Stranded Bare Copper
Insulation	4 x 1.50	1.50 (± 0.13)	RED, Black, White and Blue PVC Insulation
Jacket OD	4.80	4.80 (± 0.30)	PVC Jacket

CHARACTERISTICS

ITEM	DESCRIPTION	STANDARD
Conductor Resistance	20°C conductor DC Resistance	< 5.08 Ω / 100M
Rated Temperature		70°C
Insulation Resistance		300V

AUSTRALIAN COMPLIANCE

AS/NZS60950:2000 + A1
AS/ACIF S008:2001
AS/NZS3191:1996 Clause 3.8 (Combustion Propagation)

ACA SUPPLIER CODE:



To view Access' extensive ranges go to: www.accesscomms.com.au